



### SMARPOD P-CLL

The **SMARPOD** P-CLL uses SLC positioners for the movement in the Y-direction and a CLL stage in the X-direction. Due to this specific combination of different linear stages, the P-CLL offers an extremely large travel range in the X-direction of up to 1200 mm on demand, while maintaining a small footprint in the Y-direction.

Values for rotational travel are given for a pivot point at the surface of the top plate.

The overall dimensions of the complete system may be larger for different poses. For more information, see the CAD model in the download area.

The repeatability is measured about 20 mm above the top plate of each system, over the full travel range and for a single degree of freedom at a time. Values may be better for shorter travel ranges.

For other sizes and travels, please feel free to [contact us](#) anytime.

The large-size **SMARPOD** utilizes three carriages of the CLL-series offering an extremely large travel range of 330 mm in X-direction.

	Mechanical
Travel [mm]	330 (X); 62 (Y); 17 (Z)
Travel [°]	33 (Θx); 33 (Θy); 36 (Θz)
Max. Normal Force [N]	4
Max. Horizontal Force [N]	2
Dimensions Base Plate [mm]	554 x 45
Height of Platform above Ground [mm]	72
Weight [g]	2900
	Closed-Loop
Sensor Types	SC
Smallest Increment [nm]	1
Smallest Increment [μ°]	3

Uni-Directional Repeatability MCS2 [nm]	± 100
	Options
Vacuum Options	HV (1E-6 mbar); UHV (1E-11 mbar)
Non-Magnetic Option	--