



### CLS-3282 - Linear Stage with EDU

Linear stages of the CLS-Series have been especially designed for high availability applications in science and industry. They are equipped with SmarActs Exchangeable Drive-Units which guarantees an easy access to the stages core component, the piezo-drive which makes servicing an easy task. The Drive-Unit can be exchanged without the need to remove the complete device from the surrounding positioning setup. They are the perfect option whenever modularity and easy configuration are the top level requirements.

From a performance point of view the CLS-3282 stages are on par with their SLS-3282 counterparts. [Learn more ...](#)

The longest stage of the CLS-32 Series offer a travel range of 51 mm while maintainig a footprint of only 32 x 82 mm<sup>2</sup> and is able to handle payloads of up to 30 N.

	Mechanical
Travel [mm]	51
Blocking Force [N]	≥ 3.5
Max. Normal Force [N]	30
Max. Lift Force [N]	> 1.5
Dimensions [mm]	32 x 82 x 11
Weight [g]	87
	Open-loop
Velocity [mm/s]	> 20
Resolution [nm]	< 1
	Closed-Loop
Closed-Loop Resolution MCS2 [nm]	1 (S), 4 (L)
Closed-Loop Repeatability, Full Stroke MCS2 [nm]	±50, ±100
Closed-Loop Resolution (H)CU [nm]	4 (L)
Closed-Loop Repeatability, Full Stroke (H)CU [nm]	± 1000 (L)
	Options
Material Options	Aluminum base as standard; Titanium base (-TI)
Vacuum Options	HV (1E-6 mbar); UHV / UHVT (1E-11 mbar)