

SLC-1750 - Linear Piezo Stage

The SLC-1750 offers a travel range of 31 mm and a normal force of 30 N with dimensions of 50 x 17 x 8.5 mm.

Please note that the downloadable documents for this linear piezo stage show the dimensions and specifications of an SLC-1750 for atmospheric or HV environments, equipped with an S-position sensor. For technical drawings and detailed specifications of other variants, such as UHV compatible stages, stages with higher blocking force or other sensor options, please contact us at any time.
Travel range: 31 mm Length: 50 mm Weight: 32 g

	Mechanical
Scan Range [µm]	> 1.3
Travel [mm]	31
Blocking Force [N]	≥ 3.5
Max. Normal Force [N]	30
Max. Lift Force [N]	> 1.5
Dimensions [mm]	50 x 17 x 8.5
Weight [g]	32
	Open-loop
Velocity [mm/s]	> 20
Open-Loop Resolution MCS2 [nm]	< 1
Open-Loop Resolution (H)CU [nm]	< 50
	Closed-Loop
Sensor Resolution MCS2 [nm]	1 (S), 4 (L)
Sensor Resolution (H)CU [nm]	100 (L)
Uni-Directional Repeatability MCS2 [nm]	± 40 (S,L)
Uni-Directional Repeatability (H)CU [nm]	± 200 (L)
	Options

Copyright © 2026 SmarAct GmbH • All Rights Reserved.
SmarAct GmbH | Schuette-Lanz-Strasse 9 | 26135 Oldenburg | Germany T: +49 441 – 800 879 0 | Email: info-de@smaract.com

Material Options	Aluminum base as standard; Steel base (-ST); Titanium base (-TI); Black anodized (-BK)
Mechanical Options	U-shaped base for higher mechanical strength (-W): width is 6 mm larger; cage-creep-free guideways (-Z)
Performance Options	Higher blocking force (-D): +1.5 N
Cryogenic Option	Yes (only open loop, travel restricted to 31 mm)
Vacuum Options	HV (1E-6 mbar); UHV (1E-11 mbar)
Non-Magnetic Option	Yes, changes of the slide hole pattern apply: all threaded holes

Copyright © 2026 SmarAct GmbH • All Rights Reserved.
SmarAct GmbH | Schuette-Lanz-Strasse 9 | 26135 Oldenburg | Germany T: +49 441 – 800 879 0 | Email: info-de@smaract.com