

SLC-24150 - Linear Piezo Stage

With 103 mm, the SLC-24150 features the second longest travel range within the SLC-24 series. It measures 150 x 24 x 10.5 mm and offers a normal force of 30 N.

Please note that the downloadable documents for this linear piezo stage show the dimensions and specifications of an SLC-24150 for atmospheric or HV environments, equipped with an S-position sensor. For technical drawings and detailed specifications of other variants, such as UHV compatible stages, stages with higher blocking force or other sensor options, please feel free to contact us at any time.
Travel range: 103 mm Length: 150 mm Weight: 180 g

	Mechanical
Scan Range [µm]	> 1.3
Travel [mm]	103
Blocking Force [N]	≥ 3.5
Max. Normal Force [N]	30
Max. Lift Force [N]	1.5
Dimensions [mm]	150 x 24 x 10.5
Weight [g]	180
	Open-loop
Velocity [mm/s]	> 20
Open-Loop Resolution MCS2 [nm]	< 1
Open-Loop Resolution (H)CU [nm]	< 50
	Closed-Loop
Sensor Resolution MCS2 [nm]	1 (S), 4 (L)
Sensor Resolution (H)CU [nm]	100 (L)
Uni-Directional Repeatability MCS2 [nm]	± 40 (S,L)
Uni-Directional Repeatability (H)CU [nm]	± 200 (L)
	Options

Copyright © 2026 SmarAct GmbH • All Rights Reserved.
SmarAct GmbH | Schuette-Lanz-Strasse 9 | 26135 Oldenburg | Germany T: +49 441 – 800 879 0 | Email: info-de@smaract.com

Material Options	Aluminum base as standard; Steel base (-ST); Titanium base (-TI); Black anodized (-BK)
Mechanical Options	U-shaped base for higher mechanical strength (-W): width is 6 mm larger; cage-creep-free guideways (-Z)
Performance Options	Higher blocking force (-D): +1.5 N
Cryogenic Option	--
Vacuum Options	HV (1E-6 mbar); UHV (1E-11 mbar)
Non-Magnetic Option	Yes. Changes of the slide hole pattern apply: all threaded holes

Copyright © 2026 SmarAct GmbH • All Rights Reserved.
SmarAct GmbH | Schuette-Lanz-Strasse 9 | 26135 Oldenburg | Germany T: +49 441 – 800 879 0 | Email: info-de@smaract.com