



SMARPOD CLS-32 with Exchangeable Drive-Units

The **SMARPOD CLS-32** key feature is the [Exchangeable Drive Units](#) (EDUs) guaranteeing an easy and fast exchange of the piezo drive without the necessity to fully disassemble the positioning system. [nbsp]As an option, the base plate can be equipped with mounting posts for placing tools, sensors or other components close to the moving platform of the SMARPOD.

Values for rotational travel are given for a pivot point at the surface of the top plate.

The overall dimensions of the complete system may be larger for different poses. For more information, see the CAD model in the download area.

The repeatability is measured about 20 mm above the top plate of each system, over the full travel range and for a single degree of freedom at a time. Values may be better for shorter travel ranges.

The **SMARPOD CLS-32** is a mid-size system and is equipped with Exchangeable Drive Units, thus perfectly suited for high availability applications.

	Mechanical
Travel [mm]	20 (X); 20 (Y); 11 (Z)
Travel [°]	22 (Θx); 25 (Θy); 38 (Θz)
Max. Normal Force [N]	5
Max. Horizontal Force [N]	2.5
Dimensions [mm]	Ø 123.7
Height of Platform above Ground [mm]	53
Weight [g]	520
	Closed-Loop
Sensor Types	SC
Smallest Increment [nm]	1
Smallest Increment [μ°]	3
Uni-Directional Repeatability MCS2 [nm]	± 50
	Options

Vacuum Options	HV (1E-6 mbar); UHV (1E-11 mbar)
Non-Magnetic Option	Yes (-NM)