

## SR-2812 - 旋转台

定制的无反冲陶瓷轴承可实现极高的精度和极低的径向跳动。该阶段可提供多种选项，例如超高压真空兼容性或全非磁性版本。SR-2812 是一款小型闭环旋转台，其光阑开口为 9 毫米。

| | Mechanical |
|---|---|
| Travel [°] | ∞ |
| Blocking Torque [Ncm] | ⩾ 3 |
| Max. Normal Force [N] | 3 |
| Dimensions [mm] | 37.5 x 30 x 12 |
| Weight [g] | 35 |
| Aperture [mm] | 9 |
| | **Open-loop** |
| Angular Velocity [°/s] | > 30 |
| Open-Loop Resolution (H)CU [µ°] | < 100 |
| Open-Loop Resolution MCS2 [µ°] | < 2 |
| | **Closed-Loop** |
| Sensor Types | S |
| Sensor Resolution [µ°] | 25 |
| | **Options** |
| Material Options | Aluminum as standard; steel base (-ST); titanium base (-TI); |
| Performance Options | Higher blocking torque |
| Vacuum Options | HV (1E-6 mbar); UHV (1E-11 mbar) |
| Non-Magnetic Option | Yes (-NM) |

生成规格说明书：25.11.2026 -
版权所有 © 2026 SmarAct GmbH • 保留所有权利。
**SmarAct GmbH** | Schuette-Lanz-Strasse 9 | 26135 Oldenburg | 德国 T: +49 441 – 800 879 0 | 电子邮箱：info-de@smaract.com