

SR-5014 - 旋转台

SR-
5014旋转台在设计时考虑了与SmarAct的CLS系列的兼容性，因此可以轻松安装到该系列的线性台以及CGO系列的测角仪台上。微传感器集成使旋转台SR-
5014成为SmarAct产品线中最具成本效益的闭环旋转定位器。

	Mechanical
Travel [°]	∞
Blocking Torque [Ncm]	⩾ 5
Max. Normal Force [N]	20
Dimensions [mm]	50 x 50 x 14
Weight [g]	100
Aperture [mm]	8
	Open-loop
Angular Velocity [°/s]	> 30
Open-Loop Resolution (H)CU [µ°]	< 100
Open-Loop Resolution MCS2 [µ°]	< 2
	Closed-Loop
Sensor Types	L, S
Sensor Resolution [µ°]	15
	Options
Material Options	Aluminum as standard; steel base (-ST); titanium base (-TI);
Performance Options	Higher blocking torque
Vacuum Options	HV (1E-6 mbar)
Non-Magnetic Option	--

生成规格说明书：24.11.2026 -
版权所有 © 2026 SmarAct GmbH • 保留所有权利。
SmarAct GmbH | Schuette-Lanz-Strasse 9 | 26135 Oldenburg | 德国 T: +49 441 – 800 879 0 | 电子邮箱：info-de@smaract.com